

Chen Hsong JM Mark 6 Series Molding Machines

The JM Mark 6 Series is the next generation after the well-known JM SVP2 Series from Chen Hsong. This series takes the best features from the JM series and adds a faster and more robust platen and toggle design. The Mark 6 Series is the ultimate in reliability and flexibility at an unbelievable price!

JM88-MK6

Standard Features:

Energy Saving Inovance Servo Pumps Powerful B&R Controller

2 Core Pull Circuits

2 Air Blow Circuits

High Torque Screw Drive

Eject in Parallel with Clamp motion

Multiple Ejector Control

Precise Barrel and Nozzle Temperature Control

Electrical, Mechanical and Hydraulic Safeties

Water Flow Meters

Spare Parts Kit— Heaters Bands, Leveling Pads, Filters and Mold Clamps

CE Declaration

Euromap Standards

E67 Robot Interface

2-Year Limited Factory Warranty—Parts & Labor!

3-Year Limited Warranty on Frames & Castings

Available Options:

Special Screw and Barrel Designs—
High Mixing, Rigid PVC, PET, PMMA,
Reinforced Nylon and more
Additional Core Pull and Air Blast Circuits
including special programming
Peripheral Pump for Independent control of ejector

speed & pressure when ejecting on the fly

Shut off nozzles

Integrated Valve Gate Controls (blocks of 4)
Integrated Hot Runner Controls (blocks of 8)
High Heat Packages

Apex Sprue Pickers or 3-Axis Servo Robots (5-Axis Units available as well for 3-plate molds)



60 Years of Focus, Determined to Continue Innovating

<u>JM 88 Mark 6 Series</u>

	Unit of Measure	Α	В	С
INJECTION UNIT				
Screw Diameter	Inches	1.22	1.41	1.61
	mm	31	36	41
Screw L/D ratio	L/D	24.4	21	18.4
Shot volume	In ³	8.29	11.16	14.52
Shot size (PS)	Ounces	4.4	5.9	7.6
	Grams	124	167	216
Inj. Pressure (max)	PSI	36255	26882	20723
Inj. Rate	In³/sec	4.88	6.59	8.54
Screw Stroke	Inches (mm)	7.08 (180)		
Screw Rotation Speed (max)	RPM	280		
Nozzle Forward Force (max)	US-Tons	4.62		
Nozzle Stroke	Inches (mm)	10.82 (275)		

CLAMPING UNIT

Clamping Force	US-Tons	97	
Open Stroke	Inches	13.38	
Space Between Tie bars	Inches (mm)	14.17x14.17 (360x360)	
Platen Size	Inches (mm)	21.26x21.26 (540x540)	
Mold Thickness (Min-Max)	Inches (mm)	4.92-14.96 (125-380)	
Maximum Daylight	Inches (mm)	28.34 (720)	
Ejector Force	Us-Tons	3.74	
Ejector Stroke	Inches (mm)	4.72 (120)	
Mold Register Hole	Inches (mm)	3.93 (100)	

POWER

System Pressure	PSI	2538
Motor Power	KW (HP)	14 (19)
Electric Heating Power	KW	8
Temperature Control Zones		3+1

OTHER INFORMATION

Machine Dimensions (L*W*H)	Inches	173x46x71
	Meters	4.4x1.2x1.8
Oil Tank Capacity	Gallon	48
Machine Weight (Approx.)	Lbs	7936